

HIGH POWER / MIXERS / DJ

SM-1860U

DJ MIXER




- ✓ 12 inputs, 8 channels assignable to 2 master outputs with independent volume controls
- ✓ USB/SD player
- ✓ CUE pre-listen and input-to-output mapping matrix

ESPECIALLY RECOMMENDED IN:



Hospitality



Sports facilities

DESCRIPTION

Professional 12-input, 8-channel DJ mixer (3 microphones and 5 lines) with USB/SD player, assignable to 2 master outputs with independent volume control. Talk over function and pre-listen via headphones.

Ideal for gyms, sports pavilions, multipurpose rooms, among others.

TECHNICAL CHARACTERISTICS



+ Info:
<https://fonestar.com/SM-1860U>

FEATURES	Professional mixer with 12 inputs, 8 channels, assignable to 2 master outputs with independent volume control. USB/SD player.
PLAYER	Plays MP3 files from USB / SD or from the PC USB port for connection of USB memories and connection to PC as a USB device Audio SD card reader Information ID3 tag
INPUTS	1 balanced combo mic (XLR and 6.3 mm jack), 1,700 Ohm 10 mV RMS, 2 balanced XLR mics, 1,700 Ohm 10 mV RMS. 7 stereo unbalanced lines 22,000 Ohm 200 mV RMS and 2 phono / aux 2 x RCA 47,000 Ohm 4 mV RMS / 47,000 Ohm 200 mV RMS
CONTROLS	MIC1: volume, bass (± 12 dB, 100 Hz), treble (± 12 dB, 10,000 Hz), echo and talkover effect MIC2 and MIC3: volume, bass (± 12 dB, 100 Hz), treble (± 12 dB, 10,000 Hz) and echo effect Input channels: input selector, volume slider, assignment to master 1, master 2 and headphone preview, assignment light for each Master 1 and master 2 output: volume, bass (+12, - 32 dB, 100 Hz), mid (+12, -32 dB, 1,500 Hz) and treble (+12, -32 dB, 10,000 Hz), mid and treble, balance and level indicator Booth output: volume control Output headphone: volume control USB / SD player: play / pause, menu access, equalization and repeat mode, song forward and backward and volume control.
FUNCTIONS	Assignment matrix of 5 input channels to 2 master outputs Assignable CUE headphone preview for each channel 3-band equalizer on master outputs Master 1 and master 2 output level LEDs Talk over for level reduction on MIC 1 input
OUTPUTS	Master 1 (2 x XLR and 2 x RCA), master 2 (2 x RCA), recording (2 x RCA), booth (2 x RCA) and stereo headphones (6.3 mm jack)
RESPONSE	20-20,000 Hz
S/N RATIO	Micro: 75dB Phono: 55 dB Line / Aux: 75 dB
POWER SUPPLY	230/115 V AC, 10 W maximum
DIMENSIONS	483 x 89 x 205 mm depth. 2 U 19" rack
WEIGHT	4 kg



+ Info:
<https://fonestar.com/SM-1860U>